

# 1000kW Resistive Load Bank



## Key Features

Available in offloadable, trailer mounted or castor mounted options

Weatherproof enclosure

Vertical discharge available.

Also available in 60Hz frequency

Hardwire bus bar connections

Power terminals located behind a dedicated door

Emergency stop disconnect switch for isolation of the fan & control supply

## Options

MV cabling

Transformers

Full installation & testing

Auxiliary power supplied by generator.

KEY DATA	
RATING	1077kW (415v/3ph/50hz)
	1000kW (400v/3ph/50hz)
	903kW (380v/3ph/50hz)
	360kW (240v/1ph/50hz)*
TERMINALS PER PHASE	3x M12
FAN MOTOR SIZE, 50HZ (DOL)	4.5kW (three phase)
AIRFLOW	8.3m <sup>3</sup> /s
DEFAULT AIRFLOW DISCHARGE	Horizontal
AVERAGE AIR TEMPERATURE RISE	120°C
AUXILIARY POWER SUPPLY	32a Three Phase (CEEForm)
NOISE LEVEL (50HZ)	73dBA @ 3m (+/-3)
DIMENSIONS	
LENGTH	2.34m
WIDTH	1.54m
HEIGHT (ON BASE)	2.075m
APPROX. WEIGHT	1420kg

Specification sheets to be used as a guide only & subject to availability of the exact model described.  
If you require certain specification, please state this at the time of order.