

600kW Resistive Load Bank



Key Features

Available in offloadable, trailer mounted or castor mounted options

Weatherproof enclosure

Vertical discharge available.

Also available in 60Hz frequency

Hardwire bus bar connections

Power terminals located behind a dedicated door

Emergency stop disconnect switch for isolation of the fan & control supply

Options

MV cabling

Transformers

Full installation & testing

Auxiliary power supplied by generator.

KEY DATA	
RATING	638kW (415v/3ph/50hz)
	593kW (400v/3ph/50hz)
	535kW (380v/3ph/50hz)
	213kW (240v/1ph/50hz)*
TERMINALS PER PHASE	2x M12
FAN MOTOR SIZE, 50HZ (DOL)	2.5kW (three phase)
AIRFLOW	6.5m ³ /s
DEFAULT AIRFLOW DISCHARGE	Horizontal
AVERAGE AIR TEMPERATURE RISE	92°C
AUXILIARY POWER SUPPLY	32a Three Phase (CEEForm)
NOISE LEVEL (50HZ)	73dBA @ 3m (+/-3)
DIMENSIONS	
LENGTH	2.04m
WIDTH	1.54m
HEIGHT (ON BASE)	1.62m
APPROX. WEIGHT	950kg

Specification sheets to be used as a guide only & subject to availability of the exact model described.
If you require certain specification, please state this at the time of order.