

2100kVA Diesel Generator



Key Features

2100kVA three phase diesel generator
 Full emission compliant engine
 Available in offloadable or trailer mounted options
 Automatic/Remote start control panel
 Acoustic & weatherproof enclosure
 Fully Bunded
 Connections for external bulk fuel tank
 Lockable service access doors
 Hardwire bus bar connections
 Extended service intervals

Options

Remote fuel management
 Bulk fuel tank for extended run time
 Socket panel
 Battery charger
 Water jacket heater
 Remote telematics
 Also available in 60Hz frequency
 Optional extended run fuel tanks, both internal or external

KEY DATA	
PRIME POWER RATING	2000kVA
STANDBY POWER RATING	2180kVA
STANDARD VOLTAGE	480v
FREQUENCY	60Hz
RATED POWER FACTOR	0.8
FUEL TYPE	Diesel
FUEL CAPACITY	4540L
FUEL CONSUMPTION (AT 75% PRIME LOAD)	378.52L/hr
CONTROL PANEL MODEL	DSE8610 or CAT EMCP
SOUND LEVEL	Standby rating @16 m (50 ft) dBA 72
DIMENSIONS	
LENGTH	12.20m
WIDTH	2.34m
HEIGHT	2.90m
WET WEIGHT	33,240kg
DRY WEIGHT	28,700kg

Specification sheets to be used as a guide only & subject to availability of the exact model described.
 If you require certain specification, please state this at the time of order.