

6300kVA Transformer



Key Features

- High efficiency
- Easy to install & transport
- Easy connections
- Available in offloadable or trailer mounted Full installation options
- Acoustic & weatherproof enclosure
- Also available in 60Hz frequency
- Lockable service access doors

Options

- LV cabling
- MV cabling
- Power generation package

KEY DATA

| | | |
|----------------|---|-----------|
| NOMINAL POWER | 6300kVA | |
| FREQUENCY | 50Hz | 60Hz |
| INPUT VOLTAGE | 400Vac | 480Vac |
| INPUT CURRENT | 9093a | 7577a |
| OUTPUT VOLTAGE | 5-22kV | 6-24kV |
| OUTPUT CURRENT | 727a-165a | 606a-151a |
| VECTOR | YNyn0/Dyn11 | |
| COOLING METHOD | Oil | |
| PROTECTION | Temperature, Pressure, Gas Presence, Over Current | |
| DIMENSIONS | | |
| ENCLOSURE | 20ft Container | |
| LENGTH | 6.058m | |
| WIDTH | 2.438m | |
| HEIGHT | 2.896m | |
| WEIGHT | 21,860kg | |

Specification sheets to be used as a guide only & subject to availability of the exact model described.
If you require certain specification, please state this at the time of order.