

# Medium Voltage Load Banks



## Key Features

Available in offloadable, trailer mounted or castor mounted options

Weatherproof enclosure

Vertical discharge available.

Also available in 60Hz frequency

Hardwire bus bar connections

Power terminals located behind a dedicated door

Emergency stop disconnect switch for isolation of the fan & control supply

## Options

MV cabling

Transformers

Full installation & testing

Auxiliary power supplied by generator.

KEY DATA	
STANDARD CAPACITY RATING	2750kVA (per unit)
STANDARD LOAD STEP RESOLUTION	1kW / 1kVAR
STANDARD VOLTAGE RATINGS	690v-24,000v
FREQUENCY	50/60Hz
TERMINALS PER PHASE	Subject to ratings
FAN MOTOR SIZE, 50HZ (DOL)	Subject to ratings
AIRFLOW	Subject to ratings
DEFAULT AIRFLOW DISCHARGE	Vertical
AVERAGE AIR TEMPERATURE RISE	Subject to ratings
AUXILIARY POWER SUPPLY	Subject to ratings
NOISE LEVEL (50HZ)	85dBA @ 3m (+/-3)
DIMENSIONS	
LENGTH	6.10m
WIDTH	2.44m
HEIGHT	2.59m
APPROX. WEIGHT	Subject to ratings

Specification sheets to be used as a guide only & subject to availability of the exact model described.  
If you require certain specification, please state this at the time of order.