

# 200kVA Diesel Generator (Stage 5)

HRFW-200 T5 S5



## Key Features

- 200kVA 3 phase generator
- Stage 5 emissions compliant
- Automatic/remote start control panel
- Acoustic and weatherproof enclosure
- Fully bunded connections for external bulk fuel tank
- Lockable service access doors
- Hardwire bus bar connections
- Extended service intervals

## Options

- Remote fuel management
- Bulk fuel tank for extended run time
- Socket panel
- Remote telematics
- Battery charger
- Water jacket heater
- Also available in 60Hz frequency

### KEY DATA

PRIME POWER RATING	200kVA
STANDBY POWER RATING	220kVA
STANDARD VOLTAGE	400/230v
FREQUENCY	50Hz
RATED POWER FACTOR	0.8
FUEL TYPE	Diesel
FUEL CAPACITY	580L
FUEL CONSUMPTION @ 70% LOAD	29.7L/Hr*
CONTROL PANEL MODEL	DeepSea
SOUND LEVEL	<66dB @ 7m
LENGTH	4m
WIDTH	1.19m
HEIGHT (ON BASE)	2m
APPROX. WEIGHT	3045kg

Specification sheets to be used as a guide only & subject to availability of the exact model described. If you require certain specification, please state this at the time of order.

\*Figures based on Stage 5 usage; standard consumption for Stage 3A is 41.9L/hr.