

330kVA Diesel Generator (Stage 5)

HRSW-330 S5 T5



Key Features

- 330kVA 3 phase generator
- Stage 5 emissions compliant
- Automatic/remote start control panel
- Acoustic and weatherproof enclosure
- Fully bundled connections for external bulk fuel tank
- Lockable service access doors
- Hardwire bus bar connections
- Extended service intervals

Options

- Remote fuel management
- Bulk fuel tank for extended run time
- Socket panel
- Remote telematics
- Battery charger
- Water jacket heater
- Also available in 60Hz frequency

KEY DATA	
PRIME POWER RATING	330kVA
STANDBY POWER RATING	330kVA
STANDARD VOLTAGE	400/230v
FREQUENCY	50Hz
RATED POWER FACTOR	0.8
FUEL TYPE	Diesel
FUEL CAPACITY	910L
FUEL CONSUMPTION @70% LOAD	50.5L/Hr*
CONTROL PANEL MODEL	DeepSea
SOUND LEVEL	<68dB @ 7m
LENGTH	4.4m
WIDTH	1.7m
HEIGHT (ON BASE)	2.4m
APPROX. WEIGHT	5100kg

Specification sheets to be used as a guide only & subject to availability of the exact model described. If you require certain specification, please state this at the time of order.

*Figures based on Stage 5 usage; standard consumption for Stage 3A is 58.7L/hr.