

250kVA Diesel Generator (Stage 5)

HRSW-250 S5



Key Features

- 250kVA 3 phase generator
- Stage 5 emissions compliant
- Automatic/remote start control panel
- Acoustic and weatherproof enclosure
- Fully bundled connections for external bulk fuel tank
- Lockable service access doors
- Hardwire bus bar connections
- Extended service intervals

Options

- Remote fuel management
- Bulk fuel tank for extended run time
- Socket panel
- Remote telematics
- Battery charger
- Water jacket heater
- Also available in 60Hz frequency

KEY DATA	
PRIME/DCP POWER RATING	250kVA
STANDBY POWER RATING	250kVA
STANDARD VOLTAGE	400/230v
FREQUENCY	50Hz
RATED POWER FACTOR	0.8
FUEL TYPE	Diesel
FUEL CAPACITY	910L
FUEL CONSUMPTION @75% LOAD	39.2L/Hr*
CONTROL PANEL MODEL	DeepSea DSE8610
SOUND LEVEL	<68dB @ 7m
LENGTH	4430mm
WIDTH	1700mm
HEIGHT (ON BASE)	2400mm
APPROX. WEIGHT DRY/WITH FUEL	4800kg/5710kg

Specification sheets to be used as a guide only and subject to availability of the exact model described. If you require certain specification, please state this at the time of order.

*Figures based on Stage 5 usage; standard consumption for Stage 3A is 55L/hr.