

500kVA Diesel Generator (Stage 5)

HRSW-500 SE



Key Features

- 500kVA 3 phase generator
- Stage 5 emissions compliant
- Automatic/remote start control panel
- Acoustic and weatherproof enclosure
- Fully bunded connections for external bulk fuel tank
- Lockable service access doors
- Hardwire bus bar connections
- Extended service intervals

Options

- Remote fuel management
- Bulk fuel tank for extended run time
- Socket panel
- Remote telematics
- Battery charger
- Water jacket heater
- Also available in 60Hz frequency

KEY DATA	
PRIME POWER RATING	500kVA
STANDBY POWER RATING	500kVA
STANDARD VOLTAGE	400v
FREQUENCY	50Hz
RATED POWER FACTOR	0.8
FUEL TYPE	Diesel
FUEL CAPACITY	999L
FUEL CONSUMPTION @ 75% LOAD	77L/Hr*
CONTROL PANEL MODEL	DeepSea DSE8610
SOUND LEVEL	<98dB @ 7m
LENGTH	4980mm
WIDTH	1900mm
HEIGHT (ON BASE)	2550mm
APPROX. WEIGHT DRY/WITH FUEL	6840kg/7839kg

Specification sheets to be used as a guide only & subject to availability of the exact model described. If you require certain specification, please state this at the time of order.