

60kVA Diesel Generator (Stage 5)

HRFW-60 T5 S5



Key Features

- 60kVA 3 phase generator
- Stage 5 emissions compliant
- Available in offload-able or trailer mounted options
- Automatic/remote start control panel
- Acoustic and weatherproof enclosure
- Fully bunded connections for external bulk fuel tank
- Lockable service access doors
- Hardwire bus bar connections
- Extended service intervals

Options

- Remote fuel management
- Bulk fuel tank for extended run time
- Socket panel
- Remote telematics
- Battery charger
- Water jacket heater
- Also available in 60Hz frequency

KEY DATA	
PRIME POWER RATING	60kVA
STANDBY POWER RATING	60kVA
STANDARD VOLTAGE	400/230v
FREQUENCY	50Hz
RATED POWER FACTOR	0.8
FUEL TYPE	Diesel
FUEL CAPACITY	216L
FUEL CONSUMPTION @70% LOAD	9.8L/Hr
CONTROL PANEL MODEL	DeepSea DSE7310 (or DSE8610)
SOUND LEVEL	<62dB @ 7m
LENGTH	2660mm
WIDTH	1110mm
HEIGHT (ON BASE)	1600mm
APPROX. WEIGHT DRY/WITH FUEL	1690kg/1906kg

Specification sheets to be used as a guide only & subject to availability of the exact model described. If you require certain specification, please state this at the time of order.

*Figures based on Stage 5 usage; standard consumption for Stage 3A is 13L/hr.